



Model 6015  
Shown in White  
with EverBrass (PVD) trim

**FEATURES**

- 42" x 60" x 20-1/4" Oval whirlpool
- Simple air-switch operation
- 1-1/4 HP single-speed pump
- Six powerful Ultra-Swirl jets
- Two air controls
- Drop-in installation
- Color-Match trim, metal upgrades available (Consult Price Book for specific colors)
- Available in White and Standard Colors (Consult Price Book for specific colors)
- Outstanding protection - Mansfield® Limited One Year Acrylic Warranty

Model No.	Description	Approx.Wt.
6015	42" x 60" x 20-1/4" Oval whirlpool. Specify color and options when ordering.	108 lbs. (49 kg)
6515	42" x 60" x 20-1/4" Oval bath. Specify color and options when ordering.	88 lbs. (40 kg)
SWP151	Factory installed In-Line heater	3 lbs. (1.3 kg)
PF1320	Chrome lift and turn drain kit	1 lbs. (.4 kg)
PF1321	Everbrass lift and turn drain kit	1 lbs. (.4 kg)
PF1335	Chrome trim upgrade	1 lbs. (.4 kg)
PF1336	Everbrass trim upgrade	1 lbs. (.4 kg)



**For more information or to order, call 800-325-4422.**  
**www.whirlpoolbathtubs.com**

# 4260 OV

## Oval Whirlpool or Bath

# PRO-FIT®

### UPGRADES

#### Factory Installed In-line Heater

- A reliable, heating control upgrade maintains water temperature at desired level and operates when flow of water is detected in the system. Features a standard plug for easy electrical connection (GFCI: 120V, 20 amp dedicated circuit required to power this heater).



#### Trim Upgrade


- This option allows an upgrade to Chrome or Everbrass (PVD) trim including jets, intake, control and air control(s).

#### Lift & Turn Drain Kit Chrome and Everbrass (PVD)



- The lift and turn drain kit provides simple and easy draining of the bathtub.



### TECHNICAL INFORMATION



Pump locations are shown for clarity. STD-standard pump location.



**Installer Note:** Due to the freeform shape of the tub shell, it is recommended that the tub be on the job before making the final cut-out for drop-in installation.

**Note:** Measurements may vary 1/4" (6.4 mm ±)

### SPECIFICATIONS

<b>Dimensions</b>	42" x 60" x 20-1/4"	<b>Number of Jets</b>	Six
<b>Material</b>	Acrylic, fiberglass reinforced	<b>Air Volume Control</b>	Two
<b>Construction</b>	Self-contained, pre-plumbed whirlpool bath	<b>Water Capacity</b>	55 gal. max., 42 gal. min. (209 liters/160 liters)
<b>Pump Motor</b>	1-1/4 HP, 1 phase, 120 volt, 60 HZ, 5.9 AMP,	<b>Floor Loading</b>	47 lbs./sq. ft. (229 kg/m <sup>2</sup> )
<b>Electrical Requirements</b>	120 volt, 20 AMP, GFCI	<b>Shipping Weight</b>	148 lbs. (67 kg)
		<b>Warranty</b>	Limited One Year

These dimensions are nominal and are subject to change without notice.

When tested for compliance to the requirement of ANSI A112.19.7M and A112.19.8M for "Whirlpool Bath Appliances" and ANSI Z124 for "Plastic Bathtub Units" the tested units are found to comply and are acceptable for listing under the Terralab Engineers, Inc. follow-up service. Listed Number 15197.

Certified for permanent electrical supply connection only.

**Mansfield®**  
performance for a lifetime™