Swirl-way® Rectangular Whirlpool or Bathtub



## Bathtub and Whirlpool Features \_

- 60" x 36" x 19-3/4" rectangular bathtub
- Sculpted armrests and lumbar backrest
- One pillow
- Two decorative handles
- Mansfield® Limited Ten Year Warranty
- Available in standard colors (white, almond, biscuit and bone)
   and premium colors (British khaki, sterling silver, black and ice gray)

## **Basic Whirlpool Features**

- Hydro-V back jet system
- Single speed pump
- 1-button electronic keypad
- Color match trim
- Dual air controls

# **Luxury Whirlpool Features**

- Hydro-V back jet system
- Variable speed pump
- 5-button electronic keypad with digital temperature readout
- Metal trim upgrades
- Chromotherapy system
- In-line heater



Model 5002LUX

# Options \_ Cable Drain

#### Lift and Turn Drain

Model #	Description		Model #	Description	
SW1319	Standard Colors		PF1320	Polished Chrome	04410-
SW1320	Polished Chrome		PF1321	Everbrass (PVD)	
SW1321	Everbrass (PVD)	+	PF1322	Brushed Nickel	
SW1322	Brushed Nickel		PF1323	Oil Rubbed Bronze	
SW1323	Oil Rubbed Bronze		SW1325	5-foot removable Apron	
SWA200	Custom Pillow				
SWP150	Factory Installed Nailing Flange	0	SWAP00	Nailing Flange Kit	Manispeda

# Whirlpool Options \_\_\_\_\_

#### **Metal Trim**

Model #	Description		Model #	Description	
SW1335	Chrome				
SW1336	Everbrass (PVD)	000	SWP151	In-line water heater	3-1111-41 
SW1337	Brushed Nickel				
SW1338	Oil Rubbed Bronze				







# **Specifications**

Model #	Description	Codes/Standards		
5502	60" X 36" X 19-3/4" Rectangular Bathtub			
5002BAS	60" X 36" X 19-3/4" Basic Whirlpool Package	U P C USPC Uspus		
5002LUX	60" X 36" X 19-3/4" Luxury Whirlpool Package	○ ○ ○ Intertek		


Specification	Description	Specification	Description
Material	Acrylic, fiberglass reinforced	Number of Jets	12
Construction	Self-contained, pre-plumbed whirlpool bath, mounted on a pre-leveled base	Water Capacity	40 gal. (min.) / 60 gal. (max.)
Pump Motor	Basic: 1.5 HP Single speed induction pump Luxury: 1.5 HP Variable speed induction pump	Floor Loading Weight	47 lbs. / sq. ft. (229 kg/m <sup>2</sup> )
Electrical Requirements	Basic: One 120V, 20 Amp, GFCI dedicated circuit. Optional heater: separate 120V, 20 Amp, GFCI dedicated circuit. Luxury: Two separate 120V, 20 Amp, GFCI dedicated circuits.	Shipping Weight	whirlpool - 140 lbs. bathtub - 120 lbs.
On/Off Control	Basic: 1-button electronic control pad Luxury: 5-button electronic control pad with digital readout showing temperature of water, speed of pump and time remaining in 20-minute cycle.	Warranty	Limited Ten Year

### **Technical Information**





If a factory installed nailing flange is added to a unit, add 1/8" (3 mm) to each side flanged. Unit is available with optional removable apron for access to pump/motor and plumbing on whirlpool baths.



STD-standard pump location is as shown.

Note: Install this product according to the installation guide.

Rough-in measurements may vary 1/4" (+/-).

These dimensions are nominal and subject to change without notice.

When tested for compliance to the requirements of ASME A112.19.7M for "Whirlpool Bath Appliances" and ANSI Z124.1.2M "American National Standard for Plastic Bathtub and Shower Units", the tested units are found to comply and are acceptable for listing under IAPMO R & T.

Certified for permanent electrical connection only.

