

Bathtub and Whirlpool Features _____

- 59-1/2" x 42" x 23" oval bathtub
- Sculpted armrests and lumbar backrest
- One pillow
- Undermount or drop-in installation
- Mansfield® Limited Ten Year Warranty
- Available in standard colors (white, almond, biscuit and bone) and premium colors (British khaki, sterling silver, black and ice gray)

Basic Whirlpool Features

- Hydro-V[™] back jet system
- Single speed pump
- 1-button electronic keypad
- Color match trim
- Dual air controls

Luxury Whirlpool Features

- Hydro-V[™] back jet system
- Variable speed pump
- 5-button electronic keypad with digital temperature readout
- Metal trim upgrades
- Chromotherapy system
- In-line heater



Options __

Cable Drain Lift and Turn Drain

Model #	Description		Model #	Description	
SW1319	Standard Colors		PF1320	Polished Chrome	0410-
SW1320	Polished Chrome		PF1321	Everbrass (PVD)	
SW1321	Everbrass (PVD)	8	PF1322	Brushed Nickel	
SW1322	Brushed Nickel		PF1323	Oil Rubbed Bronze	
SW1323	Oil Rubbed Bronze	•	SWA100	Rainbow Pillow	

Whirlpool Options _____

Metal Trim

Model #	Description		Model #	Description		
SW1335	Chrome					
SW1336	Everbrass (PVD)	800	SWP151	In-line water heater		
SW1337	Brushed Nickel					
SW1338	Oil Rubbed Bronze					






Specifications

Model #	Description	Codes/Standards		
5585	59-1/2" x 42" x 23" Oval Bathtub			
5085BAS	59-1/2" x 42" x 23" Basic Whirlpool Package	U P C USPC UU		
5085LUX	59-1/2" x 42" x 23" Luxury Whirlpool Package	® Intertek		

Specification	Description	Specification	Description
Material	Acrylic, fiberglass reinforced	Number of Jets	14
Construction	Self-contained, pre-plumbed whirlpool bath with heat-bent rigid PVC pipe, mounted on a pre-leveled base	Water Capacity	50 gal. (min.) / 70 gal. (max.)
Pump Motor	Basic: 1.5 HP Single speed induction pump Luxury: 1.5 HP Variable speed induction pump	Floor Loading Weight	47 lbs. / sq. ft. (103 kg/m ²)
Electrical Requirements	Basic: One 120V, 20 Amp, GFCI dedicated circuit. Optional heater: separate 120V, 20 Amp, GFCI dedicated circuit. Luxury: Two separate 120V, 20 Amp, GFCI dedicated circuits.	Shipping Weight	whirlpool - 155 lbs. (70 kg) bathtub - 110 lbs. (49 kg)
On/Off Control	Basic: 1-button electronic control pad Luxury: 5-button electronic control pad with digital readout showing temperature of water, speed of pump and time remaining in 20-minute cycle.	Warranty	Limited Ten Year

Technical Information



These dimensions are nominal and subject to change without notice.

When tested for compliance to the requirements of ASME A112.19.7M for "Whirlpool Bath Appliances" and ANSI Z124.1.2M "American National Standard for Plastic Bathtub and Shower Units", the tested units are found to comply and are acceptable for listing under IAPMO R & T.

Certified for permanent electrical connection only.



© 2012 Mansfield Plumbing Products, LLC