



Patents recieved or pending.

Note: Dimensional Tolerances: ±1/4"

Drop-in-Hole Size:	HSC650 76" Diameter
Operating Capacity:	170 gal
Overflow Capacity:	200 gal
Floor Loading / sq.ft.:	70.9 lbs
Cartoned Wt:	350 lbs
Cube:	118 cu. ft.

Construction: Fiberglass reinforced acrylic bath with Level Form™ full-support base

We provide products listed with Underwriters Laboratories, Inc. (UL), International Association of Plumbing and Mechanical Officials (IAPMO), and Canadian Underwriters Laboratory (CUL). Consult factory with your listing requirements.

SIGNATURE EDITION: 220 V System. Two quiet, 1 ½ HP, 3-speed pumps, each with heater; 1HP, variable speed air blower with integral air heater; Two front access LED mood lights for synchronized chromotherapy; Two digital controls with LCD display windows, low water level and water temperature sensors, 20-minute timer and automatic air channel purge cycle; Two controllers operate 3-speed pumps, air blower speed and mode (continuous, wave or pulse) and shows water temperature and time remaining.

Home Spa also includes a Sound Immersion System, an aromatherapy dispensing system with an aromatherapy sample pack, two back massage therapy zones each with jetted neck pillow, and an automatic Ozone System. Also included is a floating universal remote control that controls all functions of both whirlpool pumps, air blower, air heater, LED mood lights, jetted neck pillows, and Sound Immersion Transducers that can also be used with your TV, DVD, or CD, etc.

Signature